

WHAT IS CLAIMED IS:

1. An airbag for a motor vehicle, comprising:

two portions which form a main body of the airbag, the two portions being superimposed to have one sides opposed to each other, the two portions comprising a textile, the textile having 400 dtex or less yarn, 200 g/m² or less weight, and 2,000 or more cover factor;

a first silicone placed at least the one sides of the two portions, the first silicone comprising a thermosetting silicone; and

a second silicone interposed between the two portions at a junction, the second silicone comprising a solventless addition room-temperature-vulcanizing adhesive silicone, the second silicone having 20 or less JIS-A hardness and 800% or more initial fractural elongation after cure.

2. The airbag as claimed in claim 1, wherein the textile has 235 dtex or less yarn and 150 g/m² or less weight.

3. The airbag as claimed in claim 1, wherein the cover factor of the textile is 2,000-2,600.

4. The airbag as claimed in claim 1, wherein at least part of the junction of the two portions is sewed with thread.

5. The airbag as claimed in claim 1, wherein the first silicone is 10-100 g/m² on a basis of solid matter.

6. The airbag as claimed in claim 1, wherein the JIS-A hardness of the second silicone is 2-15.

7. The airbag as claimed in claim 1, wherein the initial fractural

106080" E4642660

elongation of the second silicone is 1,000-1,500%.

8. The airbag as claimed in claim 1, wherein the second silicone has a ratio of the initial fractural elongation to the fractural elongation after 250h treatment at 100°C after cure is 1 : 0.8 or more.

9. The airbag as claimed in claim 1, wherein the second silicone has the ratio of the initial fractural elongation to the fractural elongation after 500h treatment at 100°C after cure is 1 : 0.8 or more.

10

10. The airbag as claimed in claim 8, wherein the second silicone is 100-1,000 g/m² on a basis of solid matter.

11. The airbag as claimed in claim 8, wherein the second silicone is 0.1-1.2 mm thickness.

12. The airbag as claimed in claim 8, wherein the second silicone comprises a main agent including vinyl dimethylpolysiloxane, a cross-linking agent including hydrogen-silane-radical containing compound, a curing catalyst including platinum compound.

13. The airbag as claimed in claim 8, wherein the second silicone has 50-500 Pa·s viscosity, 5-72h cure time, and 2-24h pot life.

14. The airbag as claimed in claim 4, wherein when the textile has 250 dtex or less yarn, the thread satisfies relationships of 1) $20 \leq T \leq 80$ and 2) $2 \leq T/S \leq 8$, where T is number count of thread, and S is number of stitches (times/cm).

15. The airbag as claimed in claim 14, wherein when using needle and

09924943.08001
T.06080" E4642660

